

D-Sub DIN 41 652 · CECC 75 301-802 · IEC 60 807



Number of contacts

9-50



Turned wrap posts 0.6 x 0.6 mm

Identification	No. of contacts	Part No.	
Performance levels Explanations see page 02.26 Other performance levels on request		Performance level 3	Performance level 2
Male connector tinned metal shell with dimples	9 15 25 37 50	09 67 009 5607 09 67 015 5607 09 67 025 5607 09 67 037 5607 09 67 050 5607	09 67 009 5616 ¹⁾ 09 67 015 5616 ¹⁾ 09 67 025 5616 ¹⁾ 09 67 037 5616 ¹⁾ 09 67 050 5616 ¹⁾
Female connector tinned metal shell	9 15 25 37 50	09 67 009 4707 09 67 015 4707 09 67 025 4707 09 67 037 4707 09 67 050 4707	09 67 009 4716 ¹⁾ 09 67 015 4716 ¹⁾ 09 67 025 4716 ¹⁾ 09 67 037 4716 ¹⁾ 09 67 050 4716 ¹⁾

Male connector

Female connector

Panel cut out

	a	b _{±0.1}	c	d	e	f
9	30.9	25.0	12.5	20.5	12.0	2.74
15	39.2	33.3	12.5	28.8	12.0	2.74
25	53.1	47.0	12.5	42.5	12.0	2.76
37	69.4	63.5	12.5	59.1	12.0	2.76
50	67.0	61.1	15.4	56.3	14.8	2.76

Dimensions in mm
Mating conditions see page 02.26

¹⁾ Not normally kept in stock

D-Sub - S